

# HomeConnect 620

KEYPAD CONNECTED SMART LOCK

With Z-Wave® 700 Chipset









# **Features**

- 10-Button keypad with one-touch locking
- Featuring Smartkey® Security Technology
- Sleek, all metal design
- Z-Wave® 700 for enhanced network security, network pre-enrollment, and extended wireless range and battery life
- Backward compatible with existing Z-Wave panels and hubs
- S2 Secure Network Enrollment
- SmartStart Network Pre-Enrollment

# **User Codes**

- 250 user codes
- Control when people have access with customizable user code schedules
- MasterCode security for improved feature management

# Connected Benefits

- Lock/Unlock your doors from anywhere
- View lock status and receive notifications of your lock's activity
- Connect to other devices in the home and create scenes driven by the door lock

# Specifications

#### Electrical:

Input Power	6V (4 x AA alkaline batteries)		
Mechanical:			
Door Prep	1 ½" & 2 ½" diameter bore hole & 1" deep latch hole		
Backset	Adjustable 2 <sup>3</sup> / <sub>8</sub> " or 2 <sup>3</sup> / <sub>4</sub> "		
Door Thickness	1³∕₅" - 2 " automatic adjustment		
Faceplates	1" x 2 ½" round corner standard		
Strikes	Round corner strike 1 ½ × 2 ¾		
Latch	Round corner adjustable 2 <sup>3</sup> / <sub>8</sub> " x 2 <sup>3</sup> / <sub>4</sub> "		
Bolt	1" throw, steel deadbolt		
Door Handing	Reversible		
Cylinder	SmartKey® Keyway		
Environmental:			
Temperature Range	Exterior: -40°F to 150°F Interior: 32°F to 140°F		
Humidity	Exterior: 100% condensing Interior: 30% - 95% non-condensing		

### Finishes







Venetian Bronze 11P



Polished Brass 3



Satin Nickel 15




Venetian Bronze 11P




Polished Chrome 26

## **Dimensions**



	Interior	Exterior
Α	2 <sup>23</sup> / <sub>32</sub> " (69.1 mm)	2 <sup>13</sup> / <sub>16</sub> " (71.43 mm)
В	2 <sup>23</sup> / <sub>32</sub> " (69.1 mm)	4º/16" (115.887 mm)
С	1 <sup>15</sup> /16" (49.5 mm)	1 <sup>1</sup> / <sub>4</sub> " (31.75 mm)
D	4 <sup>19</sup> / <sub>32</sub> " (116.5 mm)	



	Interior	Exterior
Α	2 <sup>23</sup> / <sub>32</sub> " (69.1 mm)	2 <sup>25</sup> / <sub>32</sub> " (70.64 mm)
В	5 <sup>25</sup> / <sub>32</sub> " (146.6 mm)	4 <sup>5</sup> / <sub>16</sub> " (109.53 mm)
С	2 <sup>1</sup> / <sub>8</sub> " (53.97 mm)	1 <sup>1</sup> / <sub>4</sub> " (31.75 mm)
D	4 ½" (114.3 mm)	

## Easy Installation

- Replaces existing door hardware with just a screwdriver
- No hard wiring needed
- Operates on 4 x AA alkaline batteries

## Innovative Security

- BHMA Grade 2 certified
- Full 128-bit encryption security
- Features SmartKey® Security Re-Key Technology with BumpGuard™ Protection
- Revolutionary tapered deadbolt design—enables misaligned doors to lock without pulling and pushing your door shut
- Supports S2 Secure Network Enrollment



Matte Black 514

